



CERTIFICATE of Conformity

Reference No. : LCS180917034BS

Applicant : Fulton Science and Technology Lighting Co., Ltd.

Address : 7F, Building 17, Area C, Liantang Industrial Town, Shangcun
Community, Gongming, Guangming New District, Shenzhen,
Guangdong Province, China.

Trademark : **Fulton**

Product : LED Tri-Proof Light

Model(s) : SEE ANNEX I

Parameters : SEE ANNEX I

The submitted products have been tested by us with the listed standards and found in compliance with the following European Directives:

The LVD Directive 2014/35/EU

EN 60598-2-24:2013; EN 60598-1:2015+A1:2018; EN 62471:2008; EN 62493:2015;

EN 62031:2008+A1:2013+A2:2015

The tests were performed in normal operation mode. The test results apply only to the particular sample tested and to the specific tests carried out. This certificate applies specifically to the sample investigated in our test reference number only.

The CE markings as shown below can be affixed on the product after preparation of necessary technical documentation.

Other relevant Directives have to be observed.



Date of issue: October 22, 2018



Shenzhen Southern LCS Compliance Testing Laboratory Ltd.
B Area, 1-2F, Building B, Zhongyu Green High-tech Industrial Park, Wenge Road, Heshuikou, Gongming
Street, Guangming New District, Shenzhen, China
Tel: (86)755-29871520 Fax: (86)755-29871521
Http://www.lcs-cert.com Email: webmaster@lcs-cert.com





ANNEX I:

Reference No. : LCS180917034BS

Model(s):

Model	Rating	Case size LxWxH (mm)
FLT-TP- 60L15	220-240V~, 50/60Hz, 60W, IP66, ta.45°C, Class I	1500x74x64
FLT-TP- 50L15	220-240V~, 50/60Hz, 50W, IP66, ta.45°C, Class I	1500x74x64
FLT-TP- 40L15	220-240V~, 50/60Hz, 40W, IP66, ta.45°C, Class I	1500x74x64
FLT-TP- 30L15	220-240V~, 50/60Hz, 30W, IP66, ta.45°C, Class I	1500x74x64
FLT-TP- 40L12	220-240V~, 50/60Hz, 40W, IP66, ta.45°C, Class I	1200x74x64
FLT-TP- 30L12	220-240V~, 50/60Hz, 30W, IP66, ta.45°C, Class I	1200x74x64
FLT-TP- 20L6	220-240V~, 50/60Hz, 20W, IP66, ta.45°C, Class I	600x74x64
FLT-TP- 18L6	220-240V~, 50/60Hz, 18W, IP66, ta.45°C, Class I	600x74x64

